

The CDSAT Paradigm for Theory Combination in SMT

(Based on joint work with S. Graham-Lengrand and N. Shankar)

Maria Paola Bonacina

Dipartimento di Informatica
Università degli Studi di Verona
Verona, Italy, EU

CEA, Paris, France, EU

15 October 2025

(Shortened version of the invited tutorial at the 21st Int. Conf. on Computability in Europe (CiE)


Lisbon, Portugal, EU, 15 and 17 July 2025)

- ▶ SMT: Satisfiability Modulo Theory
- ▶ CDSAT (Conflict-Driven Satisfiability)
 - ▶ Allows conflict-driven reasoning in a theory union
 - ▶ Generalizes previous conflict-driven procedures
- ▶ Quantifier-free input problem: set of ground clauses

Conflict-driven decision procedures

- ▶ **Search** for a model:
 - ▶ Decide **assignments** of values to terms
 - ▶ **Propagate** consequences of assignments
 - ▶ **Conflict**: contradiction
- ▶ Perform **inferences** only to solve conflicts (or reach **unsat**):
 - ▶ **Explain** conflict by **inferences**
(steps towards a possible refutation)
 - ▶ **Learn** generated **lemma** that excludes current assignment:
avoid hitting same conflict
 - ▶ Solve conflict by amending assignment to satisfy lemma
- ▶ **Search** and **inferences** guide each other:
 - ▶ **Search** focuses **inferences** on conflicts
 - ▶ **Inferences** allow **search** to escape dead-end's

The big picture



CDSAT: most general conflict-driven reasoning procedure

- ▶ Theory $\mathcal{T} = \bigcup_{k=1}^n \mathcal{T}_k$: **predicate-sharing** theories
Disjoint if \simeq is the only shared symbol
- ▶ Decide satisfiability modulo theory and assignment (SMA):
input may include **initial assignment**
 - ▶ **Boolean assignment**: $L \leftarrow \text{true}$ (**Boolean value**)
 - ▶ **First-order assignment**: $x \leftarrow 3$ (**non-Boolean value**)
- ▶ Answer **sat** if there exists satisfying assignment including
initial one, **unsat** otherwise
- ▶ Initial assignment is relevant for parallelization, optimization
as satisfiability, quantified satisfiability (**QSMA**)

CDSAT: most general conflict-driven reasoning procedure

- ▶ Transition system: transition rules (e.g., **Decide**, **Deduce**)
- ▶ Coordinates **theory modules**:
 \mathcal{T}_k -inference system + **finite local basis**
- ▶ Offers conflict-driven control accommodating also non-conflict-driven procedures (**black-box** modules)
- ▶ The modules collaborate as **peers** on a **shared trail** Γ containing the current assignment
- ▶ Each module offers **decisions** and **deductions**
propagation, conflict detection, explanation
- ▶ **Sound**, **complete**, **terminating** under suitable hypotheses
 - ▶ **Finite global basis** from the local ones for **termination**


Assignments take center stage

- ▶ Assignments of **values** to **terms**:
 $(x > 1) \leftarrow \text{false}$, $((x > 1) \vee (y < 0)) \leftarrow \text{true}$,
 $(\text{store}(a, i, v) \simeq b) \leftarrow \text{true}$, $y \leftarrow \sqrt{2}$, $\text{select}(a, j) \leftarrow 3$
- ▶ Term and value have the same sort
- ▶ Formulas are **Boolean** terms (sort prop)
- ▶ **Plausible** assignment: does not contain $L \leftarrow \text{true}$ and $L \leftarrow \text{false}$
- ▶ **Terms** and **values** are kept separate:
term only on the left, **value** only on the right of an assignment
- ▶ $\text{select}(a, j) \leftarrow 3$ cannot be replaced by $\text{select}(a, j) \simeq 3$:
a value is not a term, is not in the signature
- ▶ What are **values**?

Theory extensions to define values

- ▶ From theory \mathcal{T}_k to **theory extension** \mathcal{T}_k^+ :
 - ▶ Add new constant symbols (and possibly axioms)
 - ▶ E.g.: add a constant symbol for every number (integers, rationals, algebraic reals)
 $\sqrt{2}$ is a constant symbol interpreted as $\sqrt{2}$
 - ▶ All \mathcal{T}_k^+ 's add true and false (all \mathcal{T}_k 's have sort prop)
 - ▶ **Trivial** if it adds only true and false
- ▶ **Values** in assignments are these constant symbols: \mathcal{T}_k -values
- ▶ \mathcal{T}_k -assignment: assigns \mathcal{T}_k -values
- ▶ **Conservative** theory extension: \mathcal{T}_k^+ -unsatisfiable implies \mathcal{T}_k -unsatisfiable

The big picture: propositional reasoning



Conflict-driven propositional satisfiability: CDCL

[Marques Silva, Sakallah: ICCAD 1996, IEEE TOC 1999]

- ▶ Candidate partial model represented as a **trail** Γ of Boolean assignments (stack)
- ▶ **Decision**: add L to Γ if $L \notin \Gamma$ and $\bar{L} \notin \Gamma$
Every decision opens new level on Γ
- ▶ **Unit propagation** detects **implied literals** and **conflict clauses**
- ▶ Resolution to **explain conflict**: learn resolvent C
- ▶ Backjump away from **conflict** to a state that satisfies C
- ▶ **First assertion clause** (or 1UIP) heuristic

CDSAT reduces to CDCL if **Bool** is the only theory in the union

CDSAT generalizes CDCL

- ▶ Transition rule **Decide**: $?L$
acceptable if $L \notin \Gamma$ and $\bar{L} \notin \Gamma$ (more later for first-order decisions)
- ▶ Transition rule **Deduce** adds **justified assignment** $J \vdash L$
with **justification** J if $J \vdash_k L$ for some \mathcal{T}_k
 $\text{level}_\Gamma(J \vdash L) = \text{level}_\Gamma(J)$ and $\text{level}_\Gamma(J) = \max\{\text{level}_\Gamma(A) \mid A \in J\}$
Deduce covers **unit propagation**: implied literal: $J \vdash L$
 $J \vdash_{\text{Bool}} L \quad J = \{C \vee L, \neg C\}$
- ▶ Input assignments on Γ at level 0 as justified assignments with empty justification: $\emptyset \vdash C$
- ▶ Trail not a stack: $J \vdash L$ may be added after assignments of higher level if multiple modules share Γ (**late propagation**)

- ▶ **Conflict:** $J \subseteq \Gamma$, $J \vdash_k L$ for some \mathcal{T}_k , and $\bar{L} \in \Gamma$
unsatisfiable assignment $E = J \cup \{\bar{L}\}$
- ▶ **Conflict state:** $\langle \Gamma; E \rangle$, $E \subseteq \Gamma$
- ▶ Transition rule **Resolve explains** E by replacing $J \vdash L$ in E with J
- ▶ Given **conflict** $E = J \uplus H$ with cube $H = \{\bar{L}_1, \dots, \bar{L}_k\}$
transition rule **LearnBackjump**
 - ▶ **Learns** $J \vdash C$ where $C = L_1 \vee \dots \vee L_k$:
 J entails C since $J \uplus H$ is unsatisfiable
 - ▶ **Backjumps** to a level m such that
 $m < \text{level}_\Gamma(H)$ (quit **conflict**) and
 $m \geq \text{level}_\Gamma(J)$ so that $J \vdash C$ can be added to Γ

First assertion clause heuristic in CDSAT

- ▶ Apply **Resolve** until **conflict** E contains only one literal \bar{L} whose level m is **max** in E
- ▶ Generalize 1UIP: **max** in E not necessarily max in Γ
- ▶ Apply **LearnBackjump** to **conflict** $E = J \uplus H$ where $H = \{\bar{L}\} \uplus H'$ and $H' = \{\bar{L}_1, \dots, \bar{L}_k\}$
- ▶ **Learn** $J \vdash C$ where $C = L_1 \vee \dots \vee L_k \vee L$ (first assertion clause)
- ▶ **Backjump** to level $n = \text{level}_\Gamma(J \uplus H')$:
 $n < \text{level}_\Gamma(H)$ as $\text{level}_\Gamma(H) = \text{level}_\Gamma(\bar{L})$ which is **max** in E
 $n \geq \text{level}_\Gamma(J)$ as $J \uplus H'$ is superset of J
- ▶ Apply **Deduce** to add $\{C\} \uplus H' \vdash L$ since $\{C\} \uplus H' \vdash_{\text{Bool}} L$

LearnBackjump may follow other heuristics (e.g., **learn and restart**)

Example where CDSAT emulates CDCL

1. $S = \{\bar{A} \vee B, \bar{A} \vee C \vee E, \bar{B} \vee D, \bar{C} \vee \bar{D}, A \vee \bar{B} \vee E, B \vee \bar{C}, F \vee \bar{E}\}$
subset of input
2. **Decide** adds $?F$ to trail Γ opening level n
3. **Deduce** adds $J \vdash \bar{E}$ with $J = \{F \vee \bar{E}, ?F\}$ to level n
since $\{F \vee \bar{E}, ?F\} \vdash_{\text{Bool}} \bar{E}$
4. Two more **Decide** create levels $n + 1$ and $n + 2$
5. Another **Decide** adds $?A$ opening level $n + 3$
6. **Deduce** adds to level $n + 3$
 $H \vdash B$ with $H = \{\bar{A} \vee B, ?A\}$
 $I \vdash C$ with $I = \{\bar{A} \vee C \vee E, J \vdash \bar{E}, ?A\}$
 $K \vdash D$ with $K = \{\bar{B} \vee D, H \vdash B\}$

Example where CDSAT emulates CDCL

- $\{\overline{C} \vee \overline{D}, \text{I} \vdash C\} \vdash_{\text{Bool}} \overline{D}$ but $\text{K} \vdash D \in \Gamma$
Conflict: $E_0 = \{\overline{C} \vee \overline{D}, \text{I} \vdash C, \text{K} \vdash D\}$
/* $\overline{C} \vee \overline{D}$ is conflict clause, not assertion clause */
- E_0 contains literals $\text{I} \vdash C$ and $\text{K} \vdash D$ of max level $(n+3)$
Resolve: $E_1 = \{\overline{C} \vee \overline{D}, \text{I} \vdash C, \overline{B} \vee D, \text{H} \vdash B\}$
/* $\overline{C} \vee \overline{D}$ and $\overline{B} \vee D$ yield $\overline{B} \vee \overline{C}$ (not assertion clause) */
- E_1 contains literals $\text{I} \vdash C$ and $\text{H} \vdash B$ of max level $(n+3)$
Resolve: $E_2 = \{\overline{C} \vee \overline{D}, \overline{A} \vee C \vee E, \text{J} \vdash \overline{E}, ?A, \overline{B} \vee D, \text{H} \vdash B\}$
/* $\overline{B} \vee \overline{C}$ and $\overline{A} \vee C \vee E$ yield $\overline{B} \vee \overline{A} \vee E$ (not assertion clause) */
- E_2 contains literals $?A$ and $\text{H} \vdash B$ of max level $(n+3)$
Resolve: $E_3 = \{\overline{C} \vee \overline{D}, \overline{A} \vee C \vee E, \text{J} \vdash \overline{E}, ?A, \overline{B} \vee D, \overline{A} \vee B\}$
/* $\overline{B} \vee \overline{A} \vee E$ and $\overline{A} \vee B$ yield $\overline{A} \vee E$ (assertion clause) */

Example where CDSAT emulates CDCL


$$E_3 = \{\overline{C} \vee \overline{D}, \overline{A} \vee C \vee E, \text{J}_\perp \overline{E}, ?A, \overline{B} \vee D, \overline{A} \vee B\}$$

?A has level $n + 3$ (max), $\text{J}_\perp \overline{E}$ has level n , and the rest has level 0

11. **LearnBackjump** jumps back to level n
adds $\text{G}_\perp(\overline{A} \vee E)$ with $G = \{\overline{C} \vee \overline{D}, \overline{A} \vee C \vee E, \overline{B} \vee D, \overline{A} \vee B\}$
12. **Deduce** adds $\text{M}_\perp \overline{A}$ with $M = \{\text{G}_\perp(\overline{A} \vee E), \text{J}_\perp \overline{E}\}$
since $\{\text{G}_\perp(\overline{A} \vee E), \text{J}_\perp \overline{E}\} \vdash_{\text{Bool}} \overline{A}$
13. **Deduce** adds $\text{N}_\perp \overline{B}$ with $N = \{A \vee \overline{B} \vee E, \text{M}_\perp \overline{A}, \text{J}_\perp \overline{E}\}$
14. **Deduce** adds $\text{P}_\perp \overline{C}$ with $P = \{B \vee \overline{C}, \text{N}_\perp \overline{B}\}$

Γ contains $\{\overline{E}, \overline{A}, \overline{B}, \overline{C}\}$ model of S

The big picture: from SAT to SMT



CDCL(\mathcal{T}): from SAT to SMT

DPLL(\mathcal{T}) later renamed CDCL(\mathcal{T}) for \mathcal{T} a single theory
[Nieuwenhuis, Oliveras, Tinelli: JACM 2006]

- ▶ CDCL + decision procedure for \mathcal{T} -satisfiability of set of \mathcal{T} -literals
- ▶ CDCL works on propositional abstraction: \mathcal{T} -atoms replaced by propositional variables
- ▶ Let $\{L_1, \dots, L_n\} \subseteq \Gamma$ and $C = \bar{L}_1 \vee \dots \vee \bar{L}_n$
 \mathcal{T} -sat procedure contributes only:
 - ▶ **\mathcal{T} -conflict** detection: if $\{L_1, \dots, L_n\}$ is \mathcal{T} -unsat
 C is conflict clause
 - ▶ **\mathcal{T} -propagation**: if $\{L_1, \dots, L_n\}$ \mathcal{T} -entails L
add L to Γ with justification $C \vee L$
 L **must be** an input literal (i.e., **not new**)

CDCL(\mathcal{T}): from SAT to SMT


- ▶ \mathcal{T} -sat procedure integrated as a **black-box**
 - ▶ That only raises a flag if it detects an inconsistency in the propositional model that CDCL is building ignoring the theory:
 - ▶ **\mathcal{T} -conflict**: $\{L_1, \dots, L_n\}$ is \mathcal{T} -unsat
 $\bar{L}_1 \vee \dots \vee \bar{L}_n$ is \mathcal{T} -valid consequence of the input
 - ▶ **\mathcal{T} -propagation**: $\{L_1, \dots, L_n, \bar{L}\}$ is \mathcal{T} -unsat
 $\bar{L}_1 \vee \dots \vee \bar{L}_n \vee L$ is \mathcal{T} -valid consequence of the input
- Never deduce anything that excludes a \mathcal{T} -model but is not a \mathcal{T} -valid consequence of the input
- ▶ Model search, trail, conflict explanation, conflict-driven reasoning remain propositional

CDSAT generalizes CDCL(\mathcal{T})

- ▶ Consider a theory union whose members are **Bool** and \mathcal{T}
- ▶ Theory modules:
 - ▶ **Bool**-module
 - ▶ **Black-box** \mathcal{T} -module:
 - ▶ Only one inference rule: $L_1, \dots, L_m \vdash \perp$
 - ▶ That invokes the \mathcal{T} -procedure to detect \mathcal{T} -unsat of a set of literals

CDSAT can use a **black-box** \mathcal{T} -module whenever a theory \mathcal{T} does not have a conflict-driven procedure

The big picture: theory combination



Classical approach to theory combination: equality sharing

Equality sharing aka Nelson-Oppen method

[Nelson, Oppen: ACM TOPLAS 1979]

- ▶ $\mathcal{T} = \bigcup_{k=1}^n \mathcal{T}_k$: disjoint theories (share \simeq and sorts)
- ▶ Decision procedure for \mathcal{T}_k -satisfiability of set of \mathcal{T}_k -literals
- ▶ Stably infinite: \mathcal{T}_k -model with infinite cardinality
- ▶ Get decision procedure for \mathcal{T} -satisfiability of set of \mathcal{T} -literals
- ▶ Combination of decision procedures as black-boxes
- ▶ By disjointness, agreement is needed on:
 - ▶ Cardinalities of shared sorts: by stable infiniteness
 - ▶ Equalities between shared terms: needs work

Equality sharing: separation

- ▶ Input set S : \mathcal{T} -literals mix symbols from the \mathcal{T}_k 's signatures
- ▶ **Separate** S into sets S_k of \mathcal{T}_k -literals sharing only \simeq and variables

Example: S contains $f(2, y) \simeq f(x, y)$

- ▶ **EUF** ($f \in \Sigma_{\text{EUf}}$) and **LIA** ($2 \in \Sigma_{\text{LIA}}$)
- ▶ Shared sort: Z ; \simeq is \simeq_Z ; $f: Z \times Z \rightarrow Z$
- ▶ **EUf**: 2 is a variable
- ▶ **LIA**: $f(2, y)$ and $f(x, y)$ are variables
- ▶ $S_{\text{EUf}} = \{w_1 \simeq f(w_2, y), w_3 \simeq f(x, y), w_1 \simeq w_3\}$
- ▶ $S_{\text{LIA}} = \{w_2 \simeq 2, w_1 \simeq w_3\}$
- ▶ **Shared variables:** $\mathcal{V}_{\text{sh}}(S) = \{w_1, w_2, w_3\}$

How CDSAT handles separation

- ▶ Input set S : \mathcal{T} -literals mix symbols from the \mathcal{T}_k 's signatures
- ▶ Each \mathcal{T}_k treats as a variable a term whose top symbol is **foreign**

Example: S contains $f(2, y) \simeq f(x, y)$
(i.e., $(f(2, y) \simeq f(x, y)) \leftarrow \text{true}$)

- ▶ **EUF** ($f \in \Sigma_{\text{EUf}}$) and **LIA** ($2 \in \Sigma_{\text{LIA}}$)
- ▶ Shared sort: \mathbb{Z} ; \simeq is $\simeq_{\mathbb{Z}}$; $f: \mathbb{Z} \times \mathbb{Z} \rightarrow \mathbb{Z}$
- ▶ **EUf**: 2 is **foreign** hence a variable
- ▶ **LIA**: f is **foreign** hence $f(2, y)$ and $f(x, y)$ are variables
- ▶ **Shared terms**:

$$\mathcal{V}_{\text{sh}}(S) = \{f(2, y) \simeq f(x, y), f(2, y), 2, f(x, y)\}$$

Equality sharing: the reduction

- ▶ Reduce the \mathcal{T} -sat problem to \mathcal{T}_k -sat problems
- ▶ S is \mathcal{T} -sat iff $\bigcup_{k=1}^n S_k$ is \mathcal{T} -sat
- ▶ **Arrangement** α : represents a **partition** of $\mathcal{V}_{\text{sh}}(S)$
- ▶ α : conjunction that contains
 - ▶ $u \simeq v$ if u and v in the same class of the partition
 - ▶ $u \not\simeq v$ otherwise
- ▶ **Combination theorem**:
 $\bigcup_{k=1}^n S_k$ is \mathcal{T} -sat iff $\exists \alpha$ s.t. $S_k \wedge \alpha$ is \mathcal{T}_k -sat ($1 \leq k \leq n$)

Equality sharing: build arrangement (convex theories)

- ▶ $\mathcal{E}_0 = \emptyset$
- ▶ $\mathcal{E}_i = \mathcal{E}_{i-1} \cup \{u \simeq v\}$ if a \mathcal{T}_k -sat procedure deduces $u \simeq v$ from $S_k \cup \mathcal{E}_{i-1}$
- ▶ If a \mathcal{T}_k -sat procedure deduces \perp from $S_k \cup \mathcal{E}_i$ for some i : return **unsat** (S is **\mathcal{T} -unsat**)
- ▶ Otherwise, let $\alpha = \mathcal{E}_q$ such that $\mathcal{E}_q = \mathcal{E}_{q-1}$ (no more equalities) and return **sat** (S is **\mathcal{T} -sat**)

Complete for **convex** theories:

\mathcal{T}_k is **convex** if

$\mathcal{T}_k \models H \supset \bigvee_{i=1}^n u_i \simeq v_i$ implies $\exists j, 1 \leq j \leq n, \mathcal{T}_k \models H \supset u_j \simeq v_j$

H : a conjunction of \mathcal{T}_k -literals

Equality sharing: build arrangement (non-convex theories)

- ▶ \mathcal{T}_k **not convex**: \mathcal{T}_k -procedure deduces $\bigvee_{j=1}^m u_j \simeq v_j$
- ▶ \mathcal{T} -procedure calls itself recursively on each subproblem obtained by adding $u_j \simeq v_j$ to current \mathcal{E}_i
- ▶ In practice: CDCL(\mathcal{T}) where \mathcal{T} -procedure is equality sharing combination [Barrett, Nieuwenhuis, Oliveras, Tinelli: LPAR 2006] [Krstić, Amit Goel: FroCoS 2007]
 - ▶ \mathcal{T} -procedure sends (propositional abstraction of) $\bigvee_{j=1}^m u_j \simeq v_j$ to CDCL
 - ▶ Reasoning about disjunction is entrusted to CDCL
 - ▶ Case $u_j \simeq v_j$ is considered when CDCL puts it on the trail
 - ▶ Sole new (i.e., non-input) literals in CDCL(\mathcal{T}): (propositional abstractions of) equalities between shared variables

Equality sharing is not conflict-driven

- ▶ Combining theories by combining procedures
- ▶ \mathcal{T}_k -procedures combined as **black-boxes**
- ▶ Generation of (disjunctions of) equalities resembles saturation (can be emulated by superposition)
- ▶ In CDCL(\mathcal{T}) where \mathcal{T} -procedure is equality sharing combination, model search, trail, conflict explanation, conflict-driven reasoning remain propositional

In order to see how CDSAT emulates Equality Sharing, let's learn more about theory modules in CDSAT

Theory modules $\mathcal{I}_1, \dots, \mathcal{I}_n$ for theories $\mathcal{T}_1, \dots, \mathcal{T}_n$

- ▶ Theory module \mathcal{I}_k for theory \mathcal{T}_k is a set of inference rules $J \vdash_k L$ where
 - ▶ J is a \mathcal{T}_k -assignment: may contain first-order assignments
 - ▶ L is a singleton **Boolean** assignment
 - ▶ If a first-order assignment to x follows from the trail it can be added as a decision (**forced decision**)
- ▶ **Local basis**: $\text{basis}_k(X)$ contains all terms that \mathcal{I}_k can generate from set of terms X

All CDSAT theory modules include **equality inferences**:

- ▶ Reflexivity: $\vdash t \simeq t$
- ▶ Symmetry: $t \simeq s \vdash s \simeq t$
- ▶ Transitivity: $t \simeq s, s \simeq u \vdash t \simeq u$
- ▶ Same value: $t \leftarrow c, s \leftarrow c \vdash t \simeq s$
- ▶ Different values: $t \leftarrow c, s \leftarrow q \vdash t \not\simeq s$

With first-order assignments, two ways to make $t \simeq s$ true:
 $(t \simeq s) \leftarrow \text{true}$ and $t \leftarrow c, s \leftarrow c$

CDSAT generalizes equality sharing

- ▶ Each \mathcal{T}_k module can place its inferences $J \vdash_k L$ as justified assignments $J \vdash L$ on the **shared trail** by **Deduce** transitions (**Deduce** covers \mathcal{T}_k -propagation)
 - ▶ Equality inferences: transitivity steps and equalities from first-order assignments contribute to build an arrangement
 - ▶ Theory specific inference rules can deduce (disjunctions of) equalities
- ▶ The \mathcal{T}_k modules cooperate to build an arrangement **publicly** on the **shared trail**
- ▶ Disjunctions are handled by the **Bool**-module by **decision** and **unit propagation** (as in CDCL)

CDSAT module for equality with uninterpreted functions

- ▶ $\Sigma_{\text{EUF}} = \langle S, F \rangle$ $\text{prop} \in S$ $\simeq_s \in F$ for all sorts $s \in S$
- ▶ **EUF⁺** may be **trivial** or add countably many values for each $s \in S \setminus \{\text{prop}\}$ used as labels of congruence classes, e.g.:
 $t_1 \leftarrow c, t_2 \leftarrow c, t_3 \leftarrow c_3, t_4 \leftarrow c_4, t_5 \leftarrow c_5$
shorter than
 $t_1 \simeq t_2, t_1 \not\simeq t_3, t_1 \not\simeq t_4, t_1 \not\simeq t_5, t_3 \not\simeq t_4, t_3 \not\simeq t_5, t_4 \not\simeq t_5$
- ▶ **Congruence:**
 - ▶ $(t_i \simeq u_i)_{i=1\dots m}, (f(t_1, \dots, t_m) \not\simeq f(u_1, \dots, u_m)) \vdash_{\text{EUF}} \perp$
 - ▶ $(t_i \simeq u_i)_{i=1\dots m} \vdash_{\text{EUF}} f(t_1, \dots, t_m) \simeq f(u_1, \dots, u_m)$
 - ▶ $(t_i \simeq u_i)_{i=1\dots m, i \neq j}, f(t_1, \dots, t_m) \not\simeq f(u_1, \dots, u_m) \vdash_{\text{EUF}} t_j \not\simeq u_j$
- ▶ **basis_{EUF}(X)**: all subterms of terms in **X** and all equalities between them

Example where CDSAT emulates equality sharing

1. $\{x \leq y, y \leq (x + g(x)), P(h(x) - h(y)), \neg P(0), g(x) \simeq 0\}$
Theory union: **LIA** \cup **EUF**
2. $S = \{x \leq y, y \leq (x + g(x)), f(h(x) - h(y)) \simeq \bullet, f(0) \not\simeq \bullet, g(x) \simeq 0\}$
 $\mathcal{V}_{\text{sh}}(S) = \{x, y, g(x), h(x), h(y), h(x) - h(y), 0\}$
3. **LIA**-module: $\{y \leq x + g(x), g(x) \simeq 0\} \vdash_{\text{LIA}} y \leq x$
Deduce: $J \vdash (y \leq x)$ (level 0)
with $J = \{y \leq x + g(x), g(x) \simeq 0\}$
/* step hidden in **black-box LIA**-procedure in equality sharing */
4. **LIA**-module: $\{x \leq y, J \vdash (y \leq x)\} \vdash_{\text{LIA}} x \simeq y$
Deduce: $H \vdash (x \simeq y)$ (level 0)
with $H = \{x \leq y, J \vdash (y \leq x)\}$

Example where CDSAT emulates equality sharing

5. **EUF**-module: $H \vdash (x \simeq y) \vdash_{\text{EUf}} h(x) \simeq h(y)$

Deduce: $I \vdash (h(x) \simeq h(y))$ (level 0)

with $I = \{H \vdash (x \simeq y)\}$

6. **LIA**-module: $I \vdash (h(x) \simeq h(y)) \vdash_{\text{LIA}} h(x) - h(y) \simeq 0$

Deduce: $K \vdash (h(x) - h(y) \simeq 0)$ (level 0)

with $K = \{I \vdash (h(x) \simeq h(y))\}$

7. **EUF**-module:

$\{f(h(x) - h(y)) \simeq \bullet, K \vdash (h(x) - h(y) \simeq 0)\} \vdash_{\text{EUf}} f(0) \simeq \bullet$
but the trail contains $f(0) \not\simeq \bullet$

EUf-conflict:

$E = \{f(h(x) - h(y)) \simeq \bullet, K \vdash (h(x) - h(y) \simeq 0), f(0) \not\simeq \bullet\}$
(level 0)

Fail returns **unsat** (nowhere to backjump to)

CDSAT can emulate equality sharing

- ▶ Each \mathcal{T}_k module can also place **decisions** on the **shared trail** by **Decide** transitions
- ▶ A \mathcal{T}_k -inference $J \vdash_k L$ from $J \subseteq \Gamma$ leads to \mathcal{T}_k -**conflict**
 $E = J \cup \{\bar{L}\}$ if $\bar{L} \in \Gamma$
- ▶ Solved by **LearnBackjump**


Example where CDSAT emulates equality sharing: variant

1. $\{x \leq y, y \leq (x + g(x)), P(h(x) - h(y)), \neg P(0), g(x) \simeq 0\}$
theories: **LIA** \cup **EUF**
2. $S = \{x \leq y, y \leq (x + g(x)), f(h(x) - h(y)) \simeq \bullet, f(0) \not\simeq \bullet, g(x) \simeq 0\}$
 $\mathcal{V}_{\text{sh}}(S) = \{x, y, g(x), h(x), h(y), h(x) - h(y), 0\}$
3. **EUF**-module: **Decide** adds $?(x \not\simeq y)$ (level 1)
4. **LIA**-module: $\{y \leq x + g(x), g(x) \simeq 0\} \vdash_{\text{LIA}} y \leq x$
Deduce: $\mathcal{J} \vdash (y \leq x)$ (level 0)
with $J = \{y \leq x + g(x), g(x) \simeq 0\}$ /* **late propagation** */
5. **LIA**-module: $\{x \leq y, \mathcal{J} \vdash (y \leq x)\} \vdash_{\text{LIA}} x \simeq y$
but the trail contains $?(x \not\simeq y)$
LIA-conflict: $E_0 = \{?(x \not\simeq y), x \leq y, \mathcal{J} \vdash (y \leq x)\}$

Example where CDSAT emulates equality sharing: variant

6. **LIA-conflict**: $E_0 = \{?(x \neq y), x \leq y, \perp(y \leq x)\}$
 $?(x \neq y)$ has level 1, the rest has level 0
7. **LearnBackjump**: back to level 0 adding $\perp(x \simeq y)$
 $H = \{x \leq y, \perp(y \leq x)\}$
the derivation continues as before

The big picture: more theory combination



Model-based theory combination (MBTC)

[de Moura, Bjørner: SMT 2007]


- ▶ Variant of equality sharing in CDCL(\mathcal{T})
- ▶ Assume \mathcal{T}_k -sat procedure builds candidate model \mathcal{M}_k (e.g., linear arithmetic)
- ▶ Share $u \simeq v$ if true in \mathcal{M}_k not necessarily \mathcal{T}_k -entailed by $S_k \cup \mathcal{E}_i$ (u and v \mathcal{T}_k -terms occurring in S_k)
- ▶ (Propositional abstraction of) $u \simeq v$ posted on trail as decision
- ▶ If \mathcal{T}_k -**conflict** ensues, undo, and update \mathcal{M}_k
- ▶ Useful to accelerate reaching **sat**

\mathcal{M}_k and conflict-driven updates remain inside **black-box** procedure

CDSAT generalizes MBTC

- ▶ All theory modules cooperate as **peers** to build a model for $\mathcal{T} = \bigcup_{k=1}^n \mathcal{T}_k$ on the **shared trail**
- ▶ A theory module \mathcal{I}_k can build a partial \mathcal{T}_k -model \mathcal{M}_k **publicly** on the **shared trail**
- ▶ \mathcal{I}_k can **deduce** an equality $u \simeq v$ that follows from assignments in \mathcal{M}_k : CDSAT modules **deduce** from first-order assignments
- ▶ If a conflict ensues, $u \simeq v$ and the first-order decisions from which it depends will be undone, and \mathcal{M}_k will be amended
- ▶ MBTC does it with a decision, because in CDCL(\mathcal{T}) only \mathcal{T} -valid consequences of the input can be deduced

The big picture: more theory combination



Extensions of equality sharing

[Tinelli, Zarba: JAR 2005] [Fontaine: FroCoS 2009]

[Jovanović, Barrett: LPAR 2010] [Toledo, Przybocki, Zohar: CADE 2025]

- ▶ Variants of equality sharing in $\text{CDCL}(\mathcal{T})$
- ▶ Equality sharing requires the theories to be **stably infinite**
- ▶ Variants allow \mathcal{T}_1 **not stably infinite**, if \mathcal{T}_2 satisfies stronger cardinality requirements
- ▶ Still combining theories by combining procedures
- ▶ Procedures combined as **black-boxes**
- ▶ Completeness approach as in equality sharing: hypotheses on theories + combination theorem

CDSAT does not require **stable infiniteness**


CDSAT and agreement on cardinalities of sorts

- ▶ CDSAT requires that there exists **leading theory**, say \mathcal{T}_1 , that
 - ▶ Has all sorts in the theory union
 - ▶ Has all cardinality constraints aggregated and enforced by \mathcal{T}_1 -module inferences
- ▶ Every \mathcal{T}_k ($k \neq 1$) has to agree with \mathcal{T}_1 on what's shared: any two \mathcal{T}_k and \mathcal{T}_j ($k \neq j$) agree
- ▶ Agreement guaranteed by theory modules **completeness** requirements:
 - ▶ \mathcal{T}_1 -module **complete**
 - ▶ \mathcal{T}_k -module ($k \neq 1$) **leading-theory-complete**
- ▶ CDSAT approach to **completeness** differs from that of (variants of) equality sharing

Examples

1. All theories **stably infinite**: \mathcal{T}_1 is fictional $\mathcal{T}_{\mathbb{N}}$ that interprets all sorts (except prop) as having the cardinality of \mathbb{N}
2. **At-most- m** cardinality constraint on sort s :
$$\forall x_0, \dots, \forall x_m. \bigvee_{0 \leq i \neq k \leq m} x_i \simeq_s x_k$$
$$x_0, \dots, x_m: m + 1 \text{ distinct variables of sort } s$$
Inference rule in the \mathcal{T}_1 -module:
$$\bigwedge_{0 \leq i \neq k \leq m} u_i \not\simeq_s u_k \vdash_{\mathcal{T}_1} \perp$$
$$u_0, \dots, u_m: \text{any } m + 1 \text{ distinct terms of sort } s$$
3. Aggregation: if \mathcal{T}_2 says **at-most- m** and \mathcal{T}_2 says **at-most- p** ,
 \mathcal{T}_1 says **at-most- $\min(m, p)$**

The big picture: conflict-driven theory reasoning



Conflict-driven satisfiability procedures in arithmetic

Generalize the CDCL pattern:

- ▶ Candidate model: theory model (e.g., LRA, LIA, NRA)
- ▶ Assignment: also to **first-order** terms
(e.g., $x \leftarrow 3$, $x < y \leftarrow \text{true}$, $z \leftarrow y + 3$)
- ▶ **Propagation**: also **evaluation** of arithmetic expressions
(e.g., $y \leftarrow 0 \vdash_{\text{LRA}} (y > 2) \leftarrow \text{false}$)
- ▶ **Explanation**: also **theory-conflicts** by **theory inferences**
- ▶ Learn lemmas that may contain **new** (non-input) atoms and may exclude first-order assignments
- ▶ Expensive theory inferences only **on demand** to respond to conflicts

Outline of GCDCL procedure for generic single theory \mathcal{T}

[McMillan, Kuehlmann, Sagiv: CAV 2009]

- ▶ Embed reasoning about disjunction into theory reasoning by generalizing to \mathcal{T} -clauses a theory reasoning inference rule for \mathcal{T} -literals
- ▶ Apply the generalized rule only to **explain conflicts**
- ▶ Devise restrictions to ensure **termination**

Achieved in GCDCL: linear rational arithmetic (**LRA**)

Linear rational arithmetic (LRA)

- ▶ Input: set S of LRA-clauses
- ▶ LRA-term: rational constant c , sum $c_1 \cdot x_1 + \dots + c_n \cdot x_n$
- ▶ LRA-clause: disjunction of $t_1 \triangleleft t_2$ literals, $\triangleleft \in \{<, \leq\}$
- ▶ $\overline{(t_1 < t_2)}$ and $\overline{(t_1 \leq t_2)}$ replaced by $t_2 \leq t_1$ and $t_2 < t_1$
- ▶ $t_1 \simeq t_2$ rewritten as $t_1 \leq t_2$ and $t_2 \leq t_1$
- ▶ Variable x with positive coefficient:
rearrange literal into upper bound $x \triangleleft t$
- ▶ Variable x with negative coefficient:
rearrange literal into lower bound $t \triangleleft x$

Linear rational arithmetic (LRA)

- ▶ Fourier-Motzkin (FM) resolution:

$$\{t_1 \leq_1 x, x \leq_2 t_2\} \vdash_{\text{LRA}} t_1 \leq_3 t_2$$

$$\leq_1, \leq_2, \leq_3 \in \{<, \leq\}$$

\leq_3 is $<$ if either \leq_1 or \leq_2 is $<$ and \leq otherwise

- ▶ Transitive closure: $\{x < -y, -y < -2\} \vdash_{\text{LRA}} x < -2$

- ▶ Linear combination of constraints:

$$\{x + y < 0, -y + 2 < 0\} \vdash_{\text{LRA}} x + 2 < 0$$

- ▶ Fourier-Motzkin algorithm:

termination guaranteed

(elim one variable at each round, finitely many variables)

but generates a doubly exponential number of constraints

[Lassez, Maher: JAR 1992]

Generalized CDCL (GCDCL) for LRA

[McMillan, Kuehlmann, Sagiv: CAV 2009]

- ▶ Generalize FM-resolution to LRA-clauses: **shadow rule** e.g.:
 $\{(b < d) \vee (c < d), d < a\} \vdash_{\text{LRA}} (b < a) \vee (c < a)$
- ▶ Generates **new** (non-input) atoms
- ▶ Applied only to **explain LRA-conflicts**
generating lemmas excluding LRA-assignments
- ▶ Add restrictions to recover **termination**:
assume fixed total ordering \prec_{LRA} on rational variables
apply inference only if the variable resolved upon is
 \prec_{LRA} -**maximum** in both premises

Independently:

[Korovin, Tsiskaridze, Voronkov: CP 2009] [Cotton: FORMATS 2010]

CDSAT module for linear rational arithmetic (LRA)

- ▶ Signature Σ_{LRA} :
 - ▶ Sorts: $S = \{\text{prop}, \mathbb{Q}\}$
 - ▶ Symbols: \simeq_s for all $s \in S$
 $1, +, <, \leq, q \cdot$ for all rational numbers $q \in \mathbb{Q}$
- ▶ Theory extension LRA^+ adds constants \tilde{q} for all $q \in \mathbb{Q}$
- ▶ Inference rules:
 - ▶ **Evaluation**: $(t_1 \leftarrow \tilde{q}_1, \dots, t_m \leftarrow \tilde{q}_m) \vdash_{\text{LRA}} l \leftarrow b$
 - ▶ **Disequality elimination**:
 $t_1 \leq x, x \leq t_2, t_1 \simeq_{\mathbb{Q}} t_0, t_2 \simeq_{\mathbb{Q}} t_0, x \not\simeq_{\mathbb{Q}} t_0 \vdash_{\text{LRA}} \perp$
detects **LRA-conflict**: no value for variable x

CDSAT module for linear rational arithmetic (LRA)

- ▶ **FM-resolution:** $\{t_1 \prec_1 x, x \prec_2 t_2\} \vdash_{\text{LRA}} t_1 \prec_3 t_2$
 $\prec_1, \prec_2, \prec_3 \in \{<, \leq\}$
 \prec_3 is $<$ if either \prec_1 or \prec_2 is $<$ and \leq otherwise
- ▶ **basis_{LRA}(X):** subterms, equalities, disequalities restricting FM-resolution to resolve on the \prec_{LRA} -maximum variable
- ▶ **Detection of empty solution space:**
 $\{y_1 \leftarrow \tilde{q}_1, \dots, y_m \leftarrow \tilde{q}_m\} \uplus E \vdash_{\text{LRA}} \perp$
for all x in E , $x \prec_{\text{LRA}} y_i$ or $x = y_i$ for some i ($1 \leq i \leq m$)
- ▶ Alternatively and in practice: **sensible** search plan that selects rational variables for decision in **\prec_{LRA} -increasing order**

For CDSAT at work on conflict-driven theory reasoning, we need:

- ▶ Acceptability of first-order decisions
- ▶ Transition rule **Deduce** beyond unit propagation and deduction of equalities between shared terms
- ▶ Transition rule to solve conflicts due to first-order decisions:
UndoClear

Let's also have a more formal look at the CDSAT trail

CDSAT trail: a sequence of assignments

- ▶ Each assignment is a **decision** $?A$ or a **justified assignment** $H \vdash A$
- ▶ **Decision**: either **Boolean** or **first-order**; opens the next level
- ▶ **Justification** of A : set H of assignments that appear before A
 - ▶ Due to an inference $H \vdash_k A$
 - ▶ Due to conflict-solving transitions
 - ▶ **Boolean** or input **first-order** assignment
 - ▶ Input assignment ($H = \emptyset$)
- ▶ Level of A : max among those of the elements of H
- ▶ A justified assignment of level 5 may appear after a decision of level 6: **late propagation**; a trail is not a stack

Acceptability of a decision

- ▶ **Boolean** decision $?L$: it suffices $L \notin \Gamma$ and $\bar{L} \notin \Gamma$
- ▶ **First-order** decision $?(u \leftarrow c)$
where c is a \mathcal{T}_k -value:
 - ▶ Trail Γ does not assign a \mathcal{T}_k -value to term u
 - ▶ $u \leftarrow c$ does not trigger a \mathcal{T}_k -inference $J \cup \{u \leftarrow c\} \vdash_k \bar{L}$
with $J \subseteq \Gamma$ and $L \in \Gamma$
 - ▶ Excluding a first-order decision that triggers an immediate conflict from which nothing can be learned

- ▶ Propagation:
 - ▶ **Boolean propagation**: e.g., unit propagation
 - ▶ **\mathcal{T}_k -propagation**: e.g., propagation of equalities when emulating equality sharing
- ▶ **\mathcal{T}_k -inferences** that **explain** a **\mathcal{T}_k -conflict** generating lemmas possibly excluding \mathcal{T}_k -assignments until the **\mathcal{T}_k -conflict** can be **detected** as a Boolean conflict on the trail:
 $J \vdash_k L$ and $\bar{L} \in \Gamma$
unsatisfiable assignment $E = J \cup \{\bar{L}\}$

CDSAT transition rule UndoClear

- ▶ The assignment of **max** level in the conflict is a first-order decision
- ▶ A first-order assignment does not have a complement that can be learned
- ▶ **UndoClear** incorporates backtracking from the level of the bad decision to the previous one
- ▶ The state has changed due to a **late propagation**
- ▶ **UndoClear** fires after a **late propagation**:
bad decision was **acceptable** prior to the **late propagation**;
causes a conflict afterwards

Example with UndoClear

$\{l_0: 2x + y \simeq 1, l_1: 2x + 2y \simeq 1\}$ subset of the input (level 0)

1. **Decide:** $?(x \leftarrow 0)$ (level 1) /* **acceptable** */
2. **Deduce:** $J \vdash (y \simeq 0)$ with $J = \{2x + y \simeq 1, 2x + 2y \simeq 1\}$ (level 0)
FM-resolution: $\{2x + y \simeq 1, 2x + 2y \simeq 1\} \vdash_{\text{LRA}} y \simeq 0$ ($l_1 - l_0$)
/* **late propagation** */
3. $\{?(x \leftarrow 0), J \vdash (y \simeq 0)\} \vdash_{\text{LRA}} 2x + y \not\simeq 1$ detects
LRA-conflict $E = \{?(x \leftarrow 0), J \vdash (y \simeq 0), 2x + y \simeq 1\}$
UndoClear: undo $?(x \leftarrow 0)$ (**max** level in E) back to level 0
4. **Decide:** $?(x \leftarrow 1/2)$ (level 1)
/* **forced decision:** **only acceptable** value for x */

Example of non-termination of FM-resolution

Infinite sequence of FM-resolutions alternating on distinct variables:

$$\begin{array}{llll} l_0 : & -2 \cdot x - y < 0 & & \\ l_1 : & x + y < 0 & & \\ l_2 : & x < -1 & & \\ l_3 : & -y < -2 & (l_0 + 2l_2) & \text{elim } x \\ l_4 : & x < -2 & (l_1 + l_3) & \text{elim } y \\ l_5 : & -y < -4 & (l_0 + 2l_4) & \text{elim } x \\ l_6 : & x < -4 & (l_1 + l_5) & \text{elim } y \\ l_7 : & -y < -8 & (l_0 + 2l_6) & \text{elim } x \\ \dots & \dots & \dots & \dots \end{array}$$

It may arise even if FM-resolution is applied only to respond to **LRA-conflicts**

Example where CDSAT emulates GCDCL

$l_0: -2 \cdot x - y < 0, l_1: x + y < 0, l_2: x < -1$ (level 0)

1. Decide: $\gamma(y \leftarrow 0)$ (level 1) /* acceptable */
LRA-conflict: $\{-2 \cdot x - y < 0, x < -1, y \leftarrow 0\}$
2. Explained by $l_0 + 2l_2: \{-y < 2 \cdot x, 2 \cdot x < -2\} \vdash_{\text{LRA}} -y < -2$
Deduce: $l_3: -y < -2$ (level 0) /* late propagation */
3. $y \leftarrow 0 \vdash_{\text{LRA}} \overline{-y < -2}$ detects LRA-conflict $\{y \leftarrow 0, -y < -2\}$
UndoClear: undo $\gamma(y \leftarrow 0)$ and back to level 0
4. Decide: $\gamma(x \leftarrow -2)$ (level 1) /* acceptable */
LRA-conflict: $\{x + y < 0, -y < -2, x \leftarrow -2\}$
5. Explained by $l_1 + l_3: \{x < -y, -y < -2\} \vdash_{\text{LRA}} x < -2$
Deduce: $l_4: x < -2$ (level 0) /* late propagation */

Example where CDSAT emulates GCDCL

- $x \leftarrow -2 \vdash_{\text{LRA}} \overline{x < -2}$ detects **LRA-conflict** $\{x \leftarrow -2, x < -2\}$
UndoClear: undo $?(x \leftarrow -2)$ and back to level 0
- Decide**: $?(y \leftarrow 3)$ (level 1) /* **acceptable** */
LRA-conflict: $\{-2 \cdot x - y < 0, x < -2, y \leftarrow 3\}$
- Explained by $l_0 + 2l_4$: $\{-y < 2 \cdot x, 2 \cdot x < -4\} \vdash_{\text{LRA}} -y < -4$
Deduce: l_5 : $-y < -4$ (level 0) /* **late propagation** */
- $y \leftarrow 3 \vdash_{\text{LRA}} \overline{-y < -4}$ detects **LRA-conflict** $\{y \leftarrow 3, -y < -4\}$
UndoClear: undo $?(y \leftarrow 3)$ and back to level 0
- Decide**: $?(x \leftarrow -3)$ (level 1) /* **acceptable** */
LRA-conflict: $\{x + y < 0, -y < -4, x \leftarrow -3\}$

Example where CDSAT emulates GCDCL

11. Explained by $l_1 + l_5$: $\{x < -y, -y < -4\} \vdash_{\text{LRA}} x < -4$
Deduce: $l_6: x < -4$ (level 0) /* late propagation */
12. $x \leftarrow -3 \vdash_{\text{LRA}} \overline{x < -4}$ detects LRA-conflict $\{x \leftarrow -3, x < -4\}$
UndoClear: undo $?(x \leftarrow -3)$ and back to level 0
13. Decide: $?(y \leftarrow -5)$ (level 1) /* acceptable */
LRA-conflict: $\{-2 \cdot x - y < 0, x < -4, y \leftarrow -5\}$
14. Explained by $l_0 + 2l_6$: $\{-y < 2 \cdot x, 2 \cdot x < -8\} \vdash_{\text{LRA}} -y < -8$
Deduce: $l_7: -y < -8$ (level 0) /* late propagation */
15. $y \leftarrow -5 \vdash_{\text{LRA}} \overline{-y < -8}$ detects LRA-conflict $\{y \leftarrow -5, -y < -8\}$
UndoClear: undo $?(y \leftarrow -5)$ and back to level 0
- ...

Example where CDSAT emulates GCDCL

- ▶ Assume $y \prec_{\text{LRA}} x$
- ▶ 2nd FM-resolution inference in the non-halting sequence:
 $\{x < -y, -y < -2\} \vdash_{\text{LRA}} x < -2$
is barred: it resolves on y when x occurs in the premises
- ▶ All GCDCL or CDSAT derivations embedding that diverging series of FM-resolution inferences are barred
- ▶ Multiple CDSAT-derivations discover that
 $l_0: -2 \cdot x - y < 0, l_1: x + y < 0, l_2: x < -1$
is **LRA-unsatisfiable**
- ▶ A simple one does it by mere **LRA-propagations** at level 0

Example where CDSAT emulates GCDCL

$l_0: -2 \cdot x - y < 0$, $l_1: x + y < 0$, $l_2: x < -1$ (level 0)

Assume $y \prec_{\text{LRA}} x$

1. **Deduce**: $l_3: -y < -2$ (level 0)

$l_0 + 2l_2: \{-y < 2 \cdot x, 2 \cdot x < -2\} \vdash_{\text{LRA}} -y < -2$

/* x is \prec_{LRA} -max variable in both premises */

2. **Deduce**: $l_4: y < 0$ (level 0) /*normal form of $-y < -2 \cdot y$ */

$l_0 + 2l_1: \{-y < 2 \cdot x, 2 \cdot x < -2 \cdot y\} \vdash_{\text{LRA}} -y < -2 \cdot y$

/* x is \prec_{LRA} -max variable in both premises */

3. **Deduce**: $l_5: 2 < 0$ (level 0)


$-l_3 + l_4: \{2 < y, y < 0\} \vdash_{\text{LRA}} 2 < 0$

/* y is \prec_{LRA} -max variable in both premises as there is no x */

4. $\emptyset \vdash_{\text{LRA}} \overline{2 < 0}$ reveals **LRA-conflict** at level 0

so that **Fail** returns **unsat**

The big picture: better conflict-driven theory reasoning



Conflict-driven satisfiability procedures for sets of \mathcal{T} -literals:

- ▶ **LIA**: Cutting-to-the-chase procedure
[Jovanović, de Moura: CADE 2011, JAR 2013]
[Bromberger et al.: CADE 2015]
- ▶ **NRA**: NLSAT
[Jovanović, de Moura: IJCAR 2012]
- ▶ Use **first-order** assignments
- ▶ **Explain conflicts** by inferences that generate **new** atoms and may exclude **first-order** assignments

Conflict-driven satisfiability procedures for sets of \mathcal{T} -clauses?

From GCDCL to MCSAT

- ▶ No need to generalize to \mathcal{T} -clauses an inference rule for \mathcal{T} -literals
- ▶ Entrust the reasoning about disjunction to CDCL
- ▶ Integrate in CDCL a conflict-driven \mathcal{T} -satisfiability procedure for sets of \mathcal{T} -literals
- ▶ CDCL(\mathcal{T})? No, it allows neither **first-order assignment** nor **new** atoms on the trail nor **\mathcal{T} -inferences** generating lemmas possibly excluding first-order assignments
- ▶ MCSAT (Model-Constructing SATisfiability)
[de Moura, Jovanović: VMCAI 2013]
[Jovanović, Barrett, de Moura: FMCAD 2013]

MCSAT (Model-Constructing SATisfiability)

- ▶ Integrate CDCL and **one** model-constructing conflict-driven \mathcal{T} -sat procedure for sets of \mathcal{T} -literals (called \mathcal{T} -plugin) that
 - ▶ Has access to the trail
 - ▶ Proposes assignments to first-order terms: \mathcal{T} -assignments
 - ▶ Computes \mathcal{T} -propagations
 - ▶ Explains \mathcal{T} -conflicts by \mathcal{T} -inferences generating lemmas possibly excluding \mathcal{T} -assignments
 - ▶ Lemma may contain **new** (i.e., non-input) atoms coming from a **finite basis** for **termination**
- ▶ CDCL and the \mathcal{T} -plugin cooperate in model construction
- ▶ Both propositional and \mathcal{T} -reasoning are conflict-driven

CDSAT generalizes MCSAT

- ▶ CDSAT generalizes MCSAT to generic union $\mathcal{T} = \bigcup_{k=1}^n \mathcal{T}_k$
- ▶ MCSAT is not a combination calculus
hence does not cover, e.g.:
 - ▶ Interaction of multiple first-order theories on the trail
 - ▶ Conflict-drivenness for more than one first-order theory
 - ▶ Combination of conflict-driven and **black-box** procedures
 - ▶ **Soundness**, **completeness**, **termination** for theory combination
 - ▶ Construction of **finite global basis** from local ones
- ▶ CDSAT does **not** require model-constructing \mathcal{T}_k -sat procedures in the sense of MCSAT

CDSAT generalizes MCSAT

- ▶ CDSAT and MCSAT have different transition systems, e.g.:
 - ▶ MCSAT evaluation mechanism $\rightsquigarrow \mathcal{T}_k$ -inferences in CDSAT
 - ▶ MCSAT explanation function $\rightsquigarrow \mathcal{T}_k$ -inferences in CDSAT
explanation function: private to \mathcal{T}_k -plugin
 \mathcal{T}_k -inferences in CDSAT: public on shared trail
- ▶ CDSAT provides foundations for instances of theory combination in MCSAT implementations, e.g.:
 $\text{Bool} \cup \text{EUF} \cup \text{LRA}$ [Jovanović, Barrett, de Moura: FMCAD 2013]
- ▶ CDSAT allows **predicate-sharing** theories
MCSAT assumes **disjoint** theories

CDSAT reduces to MCSAT if theory union contains only **Bool** and **one** theory \mathcal{T} equipped with a conflict-driven model-constructing \mathcal{T} -sat procedure for sets of \mathcal{T} -literals

Example where CDSAT emulates MCSAT

$x < y, x < z, (y < w) \vee (z < w), w < x$ (level 0)

Assume $x \prec_{\text{LRA}} y \prec_{\text{LRA}} z \prec_{\text{LRA}} w$ and a sensible search plan

1. Decide: $?(x \leftarrow 0)$ (level 1) /* acceptable */
2. Decide: $?(y \leftarrow 1)$ (level 2) /* acceptable */
/* $?(y \leftarrow 0)$ not acceptable: $\{x \leftarrow 0, y \leftarrow 0\} \vdash_{\text{LRA}} \overline{(x < y)}$ */
3. Decide: $?(z \leftarrow 1)$ (level 3) /* acceptable */
/* $?(z \leftarrow 0)$ not acceptable: $\{x \leftarrow 0, z \leftarrow 0\} \vdash_{\text{LRA}} \overline{(x < z)}$ */

LRA-conflict:

$\{x \leftarrow 0, y \leftarrow 1, z \leftarrow 1, w < x, (y < w) \vee (z < w)\}$

Equivalently: no acceptable value for w

Disjunction: case analysis by Bool-module

Example where CDSAT emulates MCSAT

- Decide:** $\exists(y < w)$ (level 4)
- Deduce:** $\exists(y < x)$ (level 4)
 $J = \{\exists(y < w), \emptyset(y < x)\}$ (level 4)
 $\{\exists(y < w), \emptyset(y < x)\} \vdash_{\text{LRA}} y < x$
/* w is $\prec_{\text{LRA-max}}$ variable in both $y < w$ and $w < x$ */
- Deduce:** $\exists(x < x)$ (level 4)
 $I = \{\emptyset(x < y), \exists(y < x)\}$ (level 4)
 $\{\emptyset(x < y), \exists(y < x)\} \vdash_{\text{LRA}} x < x$
/* y is $\prec_{\text{LRA-max}}$ variable in both $x < y$ and $y < x$ */
LRA-conflict: $E_0 = \{\exists(x < x)\}$
- Resolve:** $E_1 = \{\emptyset(x < y), \exists(y < x)\}$
- Resolve:** $E_2 = \{\emptyset(x < y), \exists(y < w), \emptyset(w < x)\}$

Example where CDSAT emulates MCSAT

9. **LearnBackjump**: back to level 0 adding $H_{\vdash}(\overline{y < w})$
 $H = \{\emptyset_{\vdash}(x < y), \emptyset_{\vdash}(w < x)\}$
/* 0 is smallest level where $\overline{y < w}$ is undefined */
10. **Deduce**: $G_{\vdash}(z < w)$ (level 0)
 $G = \{H_{\vdash}(\overline{y < w}), \emptyset_{\vdash}((y < w) \vee (z < w))\}$ (level 0)
 $\{H_{\vdash}(\overline{y < w}), \emptyset_{\vdash}((y < w) \vee (z < w))\} \vdash_{\text{Bool}} z < w$
/* shadow rule unnecessary: Bool-module handles \vee by decision and unit propagation; LRA-module reasons about LRA-literals */
11. **Deduce**: $K_{\vdash}(z < x)$ (level 0)
 $K = \{G_{\vdash}(z < w), \emptyset_{\vdash}(w < x)\}$ (level 0)
 $\{G_{\vdash}(z < w), \emptyset_{\vdash}(w < x)\} \vdash_{\text{LRA}} z < x$
/* w is $\prec_{\text{LRA-max}}$ variable in both $z < w$ and $w < x$ */

Example where CDSAT emulates MCSAT

12. **Deduce**: $M \vdash (x < x)$ (level 0)

$M = \{\emptyset \vdash (x < z), K \vdash (z < x)\}$ (level 0)

$\{\emptyset \vdash (x < z), K \vdash (z < x)\} \vdash_{\text{LRA}} x < x$

/* z is $\prec_{\text{LRA-max}}$ variable in both $x < z$ and $z < x$ */

13. **LRA-conflict**: $E_3 = \{M \vdash (x < x)\}$ (level 0)

Fail returns **unsat**

- ▶ **Deduce** covers both conflict explanation and propagation
- ▶ CDSAT can apply inferences (e.g., FM-resolution) more liberally than MCSAT

CDSAT: Conflict-driven reasoning from a theory to many

- ▶ **Conflict-driven** behavior and **black-box** integration are at odds: each conflict-driven \mathcal{T}_k -sat procedure needs to access the trail, post assignments, perform inferences, explain \mathcal{T}_k -**conflicts**, export lemmas
- ▶ Key abstraction in CDSAT: open the **black-boxes** pull out the \mathcal{T}_k -**inference systems** coordinate them in a **conflict-driven** way
- ▶ If \mathcal{T}_k has no conflict-driven \mathcal{T}_k -sat procedure: **black-box inference rule** $L_1, \dots, L_m \vdash_k \perp$ invokes the \mathcal{T}_k -procedure to detect \mathcal{T}_k -**unsat**

Theory view of an assignment

It defines what a theory sees of an assignment:

- ▶ \mathcal{T}_k -view of assignment H , written H_k :
 - ▶ \mathcal{T}_k -assignments in H : those that assign \mathcal{T}_k -values
 - ▶ $u \simeq t$ if H contains $u \leftarrow c$ and $t \leftarrow c$
 - ▶ $u \not\simeq t$ if H contains $u \leftarrow c$ and $t \leftarrow q$ with $c \neq q$

u and t of \mathcal{T}_k -sort s ($s \neq \text{prop}$)

$u \leftarrow c$ and $t \leftarrow c$ may be posted by \mathcal{T}_j ($k \neq j$) sharing s
- ▶ **Global view:**
 - ▶ The \mathcal{T} -view of H for $\mathcal{T} = \bigcup_{k=1}^n \mathcal{T}_k$
 - ▶ $H_{\mathcal{T}}$ has everything

Key notion for theory combination (MCSAT does not have it)

Theory view: example

$$H = \{x > 1, \text{store}(a, i, v) \simeq b, \text{select}(a, j) \leftarrow \text{red}, y \leftarrow -1, z \leftarrow 2\}$$

- ▶ $H_{\text{Bool}} = \{x > 1, \text{store}(a, i, v) \simeq b\}$
- ▶ $H_{\text{Arr}} = \{x > 1, \text{store}(a, i, v) \simeq b, \text{select}(a, j) \leftarrow \text{red}\}$
- ▶ $H_{\text{LRA}} = \{x > 1, \text{store}(a, i, v) \simeq b, y \leftarrow -1, z \leftarrow 2, y \neq z\}$
- ▶ $H_{\text{EUF}} = \{x > 1, \text{store}(a, i, v) \simeq b, y \neq z\}$
assuming EUF has the sort Q of the rational numbers
- ▶ A **Boolean** assignment belongs to every theory view
- ▶ **Global view**: $H \cup \{y \neq z\}$

Term u is **relevant** to \mathcal{T}_k in assignment J if

- ▶ Either u occurs in J (also as subterm), \mathcal{T}_k has the sort s of u and has values for s
- ▶ Term u is an equality $u_1 \simeq_s u_2$ s.t. u_1 and u_2 occur in J , \mathcal{T}_k has sort s , but not values for s
- ▶ Term u is a Boolean term $p(u_1, \dots, u_m)$ s.t. p is a **shared predicate** symbol (by \mathcal{T}_k and at least another theory), the u_i 's occur in J , and \mathcal{T}_k has their sorts

Key notion for theory combination (MCSAT does not have it)

Relevance: example

- ▶ $H = \{x \leftarrow 5, f(x) \leftarrow 2, f(y) \leftarrow 3\}$
- ▶ $x, y: \mathbb{Q}, \quad f: \mathbb{Q} \rightarrow \mathbb{Q}, \quad \text{LRA}$ and EUF share sort \mathbb{Q}
- ▶ $H_{\text{LRA}} = H \cup \{x \neq f(x), x \neq f(y), f(x) \neq f(y)\}$
- ▶ $H_{\text{EUF}} = \{x \neq f(x), x \neq f(y), f(x) \neq f(y)\}$
- ▶ x and y are **LRA-relevant**, not **EUF-relevant**
- ▶ $x \simeq y$ is **EUF-relevant**, not **LRA-relevant**
- ▶ **LRA** makes x and y equal/different by assigning them same/different values
- ▶ **EUF** makes x and y equal/different by assigning a truth value to $x \simeq y$

Acceptability revisited

$\Gamma_{\mathcal{T}_k}$: the \mathcal{T}_k -view of trail Γ

A \mathcal{T}_k -assignment $u \leftarrow c$ is an **acceptable** decision $?(u \leftarrow c)$ for the \mathcal{T}_k -module if

1. Term u is relevant to \mathcal{T}_k in $\Gamma_{\mathcal{T}_k}$
2. $\Gamma_{\mathcal{T}_k}$ does not assign a \mathcal{T}_k -value to term u
3. If $u \leftarrow c$ is a first-order assignment: $t \leftarrow c$ does not trigger a \mathcal{T}_k -inference $J \cup \{u \leftarrow c\} \vdash_k \bar{L}$ with $J \subseteq \Gamma_{\mathcal{T}_k}$ and $L \in \Gamma_{\mathcal{T}_k}$

CDSAT transition rule UndoDecide

- ▶ The assignment of **max** level in conflict E is a justified assignment $J \vdash L$ where J contains a first-order decision $?A$ such that $\text{level}_\Gamma(?A) = \text{level}_\Gamma(J) = \text{level}_\Gamma(E)$
- ▶ **UndoDecide** undoes $?A$, backtracks, and puts \bar{L} on the trail
- ▶ A first-order assignment does not have a complement, but its Boolean consequence does
- ▶ **Resolve** is forbidden: replacing $J \vdash L$ with J in E and undoing $?A$ by **UndoClear** can cause a loop if **Decide** reiterates $?A$

- ▶ Signature Σ_{Arr} :
 - ▶ Sorts: $S = \{\text{prop}, I, V, A\}$, I: indices, V: (array) values, A: arrays with indices of sort I and values of sort V
 - ▶ Symbols: \simeq_s for all $s \in S$, select (read), store (write)
- ▶ Theory extension Arr^+ may be **trivial** or add countably many values for each $s \in S \setminus \{\text{prop}\}$
- ▶ Inference rules corresponding to the **select-over-store** axioms:
 1. $i \simeq j \longrightarrow \text{select}(\text{store}(a, i, v), j) \simeq v$
 $\{i \simeq j, b \simeq \text{store}(a, i, v), \text{select}(b, j) \neq v\} \vdash_{\text{Arr}} \perp$
 2. $i \not\simeq j \longrightarrow \text{select}(\text{store}(a, i, v), j) \simeq \text{select}(a, j)$
 $\{i \not\simeq j, b \simeq \text{store}(a, i, v), \text{select}(b, j) \neq \text{select}(a, j)\} \vdash_{\text{Arr}} \perp$

- ▶ **Extensionality** axiom:
 $(\forall i. \text{select}(a, i) \simeq \text{select}(b, i)) \longrightarrow a \simeq b$
- ▶ Clausal form:
 $\text{select}(a, \text{diff}(a, b)) \not\simeq \text{select}(b, \text{diff}(a, b)) \vee a \simeq b$
Skolem function $\text{diff} : A \times A \rightarrow I$ captures the witness index
- ▶ Inference rule:
 $a \not\simeq b \vdash_{\text{Arr}} \text{select}(a, \text{diff}(a, b)) \not\simeq \text{select}(b, \text{diff}(a, b))$
- ▶ **basis_{Arr}(X)**: all subterms of terms in X , equalities btw them, and witness terms $\text{select}(a, \text{diff}(a, b))$, $\text{select}(b, \text{diff}(a, b))$

Example with theory clauses and UndoDecide

- ▶ Input set S contains clauses:
 - ▶ $C_1: (i \neq j) \vee (\text{select}(\text{store}(a, i, v), j) < \text{select}(a, j))$
 - ▶ $C_2: (\text{select}(a, j) - \text{select}(a, k)) \simeq 0$
 - ▶ $C_3: (\text{select}(\text{store}(a, i, v), j) \not< \text{select}(a, j)) \vee (\text{select}(a, j) + \text{select}(a, k) \simeq v)$
- ▶ Theory union: $\text{Bool} \cup \text{LRA} \cup \text{Arr}$
- ▶ Suppose Arr interprets indices as integers:
 $I = \mathbb{Z}$ and Arr^+ adds integer constants as Arr -values

Example with theory clauses and UndoDecide

1. Arr-module: Decide $?(i \leftarrow 0)$ (level 1)
/* acceptable as i is relevant to Arr */
2. Arr-module: Decide $?(j \leftarrow 0)$ (level 2)
3. Arr-module: equality inference $\{i \leftarrow 0, j \leftarrow 0\} \vdash_{\text{Arr}} i \simeq j$
Deduce: $A_1: \mathcal{J} \vdash (i \simeq j)$ with $J = \{?(i \leftarrow 0), ?(j \leftarrow 0)\}$ (level 2)
4. Bool-module: unit propagation
 $\{A_1, C_1\} \vdash_{\text{Bool}} \text{select}(\text{store}(a, i, v), j) < \text{select}(a, j)$
Deduce: $A_2: \mathcal{I} \vdash (\text{select}(\text{store}(a, i, v), j) < \text{select}(a, j))$
with $I = \{A_1, C_1\}$ (level 2)

Example with theory clauses and UndoDecide

5. Bool-module: unit propagation

$\{A_2, C_3\} \vdash_{\text{Bool}} \text{select}(a, j) + \text{select}(a, k) \simeq v$

Deduce: $A_3: H \vdash (\text{select}(a, j) + \text{select}(a, k) \simeq v)$

with $H = \{A_2, C_3\}$ (level 2)

6. Arr-module: first select-over-store rule

$\{A_1, A_2\} \vdash_{\text{Arr}} v < \text{select}(a, j)$

Deduce: $A_4: G \vdash (v < \text{select}(a, j))$

with $G = \{A_1, A_2\}$ (level 2)

7. LRA-module: FM-resolution $A_3 + C_2$

$\{A_3, C_2\} \vdash_{\text{LRA}} \text{select}(a, j) \simeq v/2$

Deduce: $A_5: M \vdash (\text{select}(a, j) \simeq v/2)$

with $M = \{A_3, C_2\}$ (level 2)

Example with theory clauses and UndoDecide

LRA-conflict: $E_0 = \{A_4, A_5\}$

as $A_4: \text{G}^+(v < \text{select}(a, j))$ and $A_5: \text{M}^-(\text{select}(a, j) \simeq v/2)$

8. E_0 contains literals A_4 and A_5 of max level (2)
Resolve: $E_1 = \{A_4, A_3, C_2\}$
9. E_1 contains literals A_3 and A_4 of max level (2)
Resolve: $E_2 = \{A_1, A_2, A_3, C_2\}$
10. E_2 contains literals A_1, A_2 and A_3 of max level (2)
Resolve: $E_3 = \{A_1, A_2, C_3, C_2\}$
11. E_3 contains literals A_1 , and A_2 of max level (2)
Resolve: $E_4 = \{A_1, C_1, C_3, C_2\}$

Example with theory clauses and UndoDecide

$$E_4 = \{A_1, C_1, C_3, C_2\}$$

E_4 contains **one** literal of max level: $\text{level}_\Gamma(A_1) = 2 = \text{level}_\Gamma(E_4)$

A_1 is $J \vdash (i \simeq j)$ and $J = \{?(i \leftarrow 0), ?(j \leftarrow 0)\}$

where $?(j \leftarrow 0)$ also has level 2

Apply **Resolve** to replace A_1 with J
and **UndoClear** to undo $?(j \leftarrow 0)$?

No, the system could loop by repeating $?(j \leftarrow 0)$
(still acceptable)

Example with theory clauses and UndoDecide

12. **UndoDecide**: $\text{undo } ?(j \leftarrow 0)$, backtrack to level 1,
and add decision $?(i \neq j)$ (level 2)
/* $C_1: (i \neq j) \vee (\text{select}(\text{store}(a, i, v), j) < \text{select}(a, j))$ is satisfied */
13. **LRA**-module: **Decide** $?(\text{select}(a, j) \leftarrow 1)$ (level 3)
14. **LRA**-module: **Decide** $?(\text{select}(a, k) \leftarrow 1)$ (level 4)
/* $C_2: (\text{select}(a, j) - \text{select}(a, k)) \simeq 0$ is satisfied */
15. **LRA**-module: **Decide** $?(v \leftarrow 2)$ (level 5)
/* $C_3: (\text{select}(\text{store}(a, i, v), j) \not< \text{select}(a, j)) \vee$
 $(\text{select}(a, j) + \text{select}(a, k) \simeq v)$ is satisfied */

Example with theory clauses and UndoDecide: variant

Suppose theory Arr does not have values for array indices:
 i and j not relevant, Arr-module cannot decide their values

1. Arr-module: Decide $?(i \simeq j)$ (level 1)
/* acceptable as $i \simeq j$ is relevant to Arr */
2. The same transitions as before lead to conflict
 $\{?(i \simeq j), C_1, C_3, C_2\}$ (level 1)
3. LearnBackjump backtracks to level 0 and places $N_{\vdash}(i \not\simeq j)$
on the trail with $N = \{C_1, C_3, C_2\}$
4. The satisfiability of the clauses can be detected as before

Current and future work

- ▶ More theory modules: maps, vectors (aka dynamic arrays), vectors with concatenation (possibly subsuming sequences and hence strings)
- ▶ Formulas with quantifiers: CDSAT(QSMA)
- ▶ CDSAT search plans: both global and local issues
 - ▶ Heuristic strategies to make decisions, prioritize theory inferences, control lemma learning
 - ▶ Efficient techniques to detect applicability of theory inference rules and acceptability of decisions
- ▶ Architecture of a CDSAT solver
- ▶ Baby verified implementation written in Rust by Xavier Denis: <https://github.com/xldenis/cdsat>

- ▶ The CDSAT method for satisfiability modulo theories and assignments: an exposition. Proc. CiE-21, LNAI 15764, 1–16, Springer, 2025.
- ▶ Conflict-driven satisfiability for theory combination: transition system and completeness. JAR, 64(3):579–609, 2020.
- ▶ Conflict-driven satisfiability for theory combination: modules, lemmas, and proofs. JAR, 66(1):43–91, 2022.
- ▶ CDSAT for predicate-sharing theories: arrays, maps, and vectors with abstract domain. In preparation.

Thank you!